

## **Op 60**

### **Drum Handlers - CDH-1 & CDH-2**

#### **Specification:**

Designed to handle Steel Drums of 200/220 litre capacity with rolling hoops and body diameter approximately 572 mm. Suitable also for American drums of 55 US gallons of similar diameter.

#### **Fitting:**

With the lower hangers removed and the attachment resting on a raised surface, drive the fork truck slowly forwards until the top of the truck carriage plate contacts the backplate of the attachment just below the top hangers. Carefully raise the mast until the top of the truck carriage plate fits snugly into the top hangers. Bolt the bottom hangers through the holes provided.

#### **Operation:**

The action of the attachment is fully automatic. The attachment has two curved arms which hinge at one end. To lift a drum, approach it with the clamp arms HORIZONTAL and positioned halfway up the drum, between the two rolling hoops. DO NOT USE REARWARD TILT OF THE MAST.

When the arms contact the drum they will open automatically, falling back around the drum as you proceed forwards. When the attachment is raised, the arms will grip the drum tightly under the upper rolling hoop. Ensure that the drum is held firmly after lifting.

To release the drum, the operator simply lowers it onto a firm surface and backs the truck away.

Avoid shock loads, and operation on rough ground. This attachment is not suitable for straight-sided, empty or damaged drums, nor drums with the head removed.  
Do not use for upending drums.

Ensure retaining screw in the pivot arm is checked for tightness every month.

All moving parts must be lubricated regularly.

A visual inspection should be carried out before each period of use.

Thorough examination of the attachment, hook, shackle and eyebolt should be carried out and recorded every six months. ('Refer to the Lifting Operations and Lifting Equipment Regulations 1998' & 'The Provision of Work Equipment Regulations 1998' for further information)

#### **Capacity:**

The maximum weight of drum which can be carried safely by each set of arms is 500 Kg.

**Consult the truck manufacturer if in doubt.**