



Rim Grip Drum Handler (PB)

Use :-

Hardened steel jaws grip the rim chimb of the drum, allowing the drums to be picked up or set down without spaces between them. Ideal for stuffing and de-stuffing containers and suitable for use on rough terrain. May be used with 120 or 210 litre drums of steel, 'L' ring or 'XL' ring plastic types. A spark proof model is available for operating in zone 1 conditions. Not for use with empty drums.



Rim Grip Drum Handlers offer fast and safe movement of drums via hardened steel jaws that grip the drum chimb (rim), allowing the drums to be picked up/set down with minimal gap between them. Ideal for stuffing/de-stuffing containers, suitable for use also on rough terrain. May be used for use with 120 or 210 litre Steel Drums and "L"/"XL" Plastic drums. A Spark Proof model is available for Zone 1 conditions. Not for use with empty drums

| Model Ref | Weight | C of G | Lost Load Centre |
|-----------|--------|--------|------------------|
| PB-1 | 78kgs | 583mm | 210mm |
| PB-2 | 102kgs | 637mm | 210mm |
| PB-1-C | 79kgs | 585mm | 340mm |
| PB-2-C | 104kgs | 638mm | 340mm |
| PB-1-SS | 78kgs | 583mm | 210mm |
| PB-2-SS | 102kgs | 647mm | 210mm |

| Model Ref | Capacity | No. Of Drums | Drum Types | "A2 Load Ctr | "B" Fork Spread | "C" Fork Width | "D" Fork Thicknes |
|-----------|----------|--------------|------------|--------------|-----------------|----------------|-------------------|
| PB-1 | 750kgs | 1 | 1 & 2 | 1244mm | 560mm | 140mm | 50mm |
| PB-2 | 1500kgs | 2 | 1 & 2 | 1244mm | 560mm | 140mm | 50mm |
| PB-1-C | 750kgs | 1 | 1 & 2 | 1244mm | 560mm | 140mm | 50mm |
| PB-2-C | 1500kgs | 2 | 1 & 2 | 1244mm | 560mm | 140mm | 50mm |
| PB-1-SS | 750kgs | 1 | 1 & 2 | 1244mm | 560mm | 140mm | 50mm |
| PB-2-SS | 1500kgs | 2 | 1 & 2 | 1244mm | 560mm | 140mm | 50mm |

Ordering Information

Truck Capacity

Fork Width/Thickness

Drum Weight

Drum Type

Max Fork Spread

Drum Diameter

