



Rim Grip Drum Handler (PB)

Our best selling tipping skip. This skip can be used for a wide variety of applications and therefore makes it a popular choice for waste handling. Designed to be placed in production areas, Roll Forward skips keep working areas clear and allow safe and speedy removal of scrap or rubbish to the appropriate waste receptacle. All CONTACT skips have unique twin locks and simple to operate release mechanism, all skips also come with a retaining security chain for fastening to the truck.



CONTACT Rim Grip Drum Handlers offer fast and safe movement of drums via hardened steel jaws that grip the drum chimb (rim), allowing the drums to be picked up/set down with minimal gap between them. Ideal for stuffing/de-stuffing containers, suitable for use also on rough terrain. May be used for use with 120 or 210 litre Steel Drums and "L"/"XL" Plastic drums. A Spark Proof model is available for Zone 1 conditions. Not for use with empty drums

Model Ref.	Weight	C of G	Lost Load Centre
PB-1	78kgs	583mm	210mm
PB-2	102kgs	637mm	210mm
PB-3	126kgs	698mm	210mm
PB-1-C	79kgs	585mm	340mm
PB-2-C	104kgs	638mm	340mm
PB-3-C	128kgs	699mm	340mm
PB-1 SP	60kgs	583mm	45mm
PB-2 SP	90kgs	647mm	45mm

Model Ref.	Capacity	No. Of Drums	Dum Types	"A" Load Ctr	"B" Fork Spread	"C" Fork Width	"D" Fork Thickness
PB-1	750kgs	1	1 & 2	1244mm	560mm	140mm	50mm
PB-2	1500kgs	2	1 & 2	1244mm	560mm	140mm	50mm
PB-3	2250kgs	3	1 & 2	1244mm	560mm	140mm	50mm
PB-1-C	750kgs	1	3	1244mm	560mm	140mm	50mm
PB-2-C	1500kgs	2	3	1244mm	560mm	140mm	50mm
PB-3-C	2250kgs	3	3	1244mm	560mm	140mm	50mm
PB-1 SP	450kgs	1	1 & 2	1331mm	500mm	145mm	50mm
PB-2 SP	900kgs	2	1 & 2	1331mm	725mm	145mm	50mm

Ordering Information

Truck Capacity
Fork Width/Thickness
Drum Weight

Drum Type
Max Fork Spread
Drum Diameter

