



Automatic Base Emptying Stillages

The automatic range of base emptying stillages is designed for most forklifts. They operate fully automatically when lowered against a waste skip, allowing contents to be dumped without the driver leaving the seat.

Supplied with legs as standard (castors optional or standard on larger models), they provide efficient waste handling in workshops and factories.

Fast, safe, and driver-friendly – ideal for dry loads.

| Measurements | Capacity (m ³) | Length (mm) | Width (mm) | Height (mm) |
|--------------|----------------------------|-------------|------------|-------------|
| ADB 50 | 0.5 | 1020 | 870 | 920 |
| ADB 70 | 0.7 | 1020 | 970 | 1080 |
| ADB 100 | 1.0 | 1320 | 1050 | 1080 |
| ADB 150* | 1.5 | 1690 | 1050 | 1080 |
| ADB 200* | 2.0 | 2000 | 1050 | 1080 |



IMPORTANT INFORMATION: These units are not designed for wet loads as they will leak from the base, which can cause overloading and potential damage to the locking mechanism.

Optional Extras

Swivel Castors

Weight (kg)

| | |
|---------|-----|
| ADB 50 | 89 |
| ADB 70 | 139 |
| ADB 100 | 165 |
| ADB 150 | 190 |
| ADB 200 | 228 |



Features & Benefits

- Manufactured from 2mm thick steel side plates and 3mm thick base plate for long service life
- Fully automatic operation – no wires or climbing required
- Base automatically locks when lowered onto solid surface
- Pallet feet for safe stacking
- Supplied with safety security chain for positive truck connection

