



Upright Side Discharge Skip

The ELEV range of upright concrete skips offers precise side discharge for controlled pouring. With a lower overall height than comparable capacities, these rectangular skips are ideal for crane or forklift handling.

Large side gate enables high-precision concrete flow and easy cleaning. Integrated fork locking system for safety.

Choose ELEV skips for efficient, reliable concrete placement on site.

Model Ref	Operation	SWL (Kg)	Capacity (Ltr)	Length (mm)	Width (mm)	Height (mm)
FCH-11033FM	Lever	720	300	1130	860	1040
FCH-11033FMVO	Hand Wheel	720	300	1130	860	1040
FCH-11033FMVH	Hydraulic	720	300	1130	860	1040
FCH-11053FM	Lever	1200	500	1130	860	1340
FCH-11053FMVO	Hand Wheel	1200	500	1130	860	1340
FCH-11053FMVH	Hydraulic	1200	500	1130	860	1340
FCH-11083FM	Lever	1920	800	1300	995	1400
FCH-11083FMVO	Hand Wheel	1920	800	1300	995	1400
FCH-11083FMVH	Hydraulic	1920	800	1300	995	1400
FCH-11103FM	Lever	2400	1000	1300	995	1600
FCH-11103FMVO	Hand Wheel	2400	1000	1300	995	1600
FCH-11103FMVH	Hydraulic	2400	1000	1300	995	1600
FCH-11123FMVO	Hand Wheel	2880	1200	1560	1120	1600
FCH-11123FMVH	Hydraulic	2880	1200	1560	1120	1600

Features & Benefits

- Dual compatibility – forklift and crane handling with lateral lifting points
- Secure forklift operation – integrated fork locking system
- Precise side discharge – large rectangular gate for controlled flow and easy cleaning
- Flexible gate control – lever, hand-wheel, or hydraulic cylinder options
- Wide capacity range – 300 to 1200 litres

