



Pallet Crane Forks - Bow & Eye Head

Our pallet crane forks enable safe lifting and movement of pallets using overhead or lorry-mounted cranes. The 'Bow & Eye' head design features notched lifting positions (800/1000/1200mm) for handling empty or loaded pallets.

The strong yet lightweight 'A' frame construction is ideal for industrial and offshore use where safety and durability are essential. No minimum pallet weight required.

Fully tested and certified for compliance.

Specification	PG100/2 SSB/B	PG120/3 SSB/B
Fork Length (mm)	970	1170
Centre of Balance (mm)	500	600
Free Height (mm)	1270 - 1900	1320 - 2010
Fork Centres (mm)	300 - 850	330 - 830
Lifting Positions (mm)	800 / 1000 / 1200	800 / 1000 / 1200
Fork Section (mm)	100 x 40	120 x 50
Maximum SWL (kg)	2000	3000
Unit Weight (kg)	150	230
SAFETY & COMPLIANCE		
Fully tested to current standards	Designed for safe overhead/lorry crane use	
CE-marked with Certificate of Conformity	Reduces manual handling risks	
No minimum pallet weight required	Fully load-tested and certified	



Typical Applications

Industrial warehouses & factories

Offshore platforms & marine environments

Construction sites & material handling

Heavy-duty pallet transfer in ports & depots

Features & Benefits

- 'Bow & Eye' head with 3 notched lifting positions for various pallet sizes
- 'A' frame design – extremely strong yet lightweight
- No minimum pallet weight required for operation
- Suitable for overhead crane or lorry-mounted crane use
- Fully tested and certified to meet health & safety regulations

