

Tipping Skips - Galvanised Range



Tipping Skips - Galvanised Range

Our Galvanised Tipping Skips are ideal for handling corrosive waste or working in corrosive environments. The hot-dipped galvanised finish provides excellent protection against rust, while maintaining the strength needed for safe and efficient waste removal.

Manufactured from 3mm gauge steel with full-width release handles and twin locking mechanisms for operator safety. They help keep working areas clear and allow speedy transfer of scrap and rubbish.

Model Ref	Volumetric Capacity (m ³)	Load Capacity (kg)	Weight (kg)
RFS 40L-GALV	0.4	1000	125
RFS 80L-GALV	0.8	1000	175
RFS 120L-GALV	1.2	1250	188



Dimensions	O/all Length (mm)	O/all Width (mm)	O/all Height (mm)	Bin Length (mm)	Bin Height (mm)	Fork Spread (mm)
* RFS 40L-GALV	1360	800	780	1195	550	890
RFS 80L-GALV	1720	960	985	1545	760	890
RFS 120L-GALV	1720	1200	985	1545	760	890

Fork Section : To suit maximum size forks 150mm x 60mm thick

* For RFS 40L model, please note the overall width is 925mm. For all other models, the bin width is the widest point

Features & Benefits

- Hot-dipped galvanised finish – excellent corrosion resistance for harsh environments
- Full-width release handle eliminates need to lean between skip & truck
- Heavy-duty underframes for long service life
- Twin locking mechanism ensures skip remains secure when loaded unevenly
- Pre-drilled castors plates for easy retro-fitment (no welding required)
- Safety security chain to ensure safe retention to lift truck

Options

Lids

Auto Release

Mesh Extensions

Castors

Lifting Lugs

Drain Tap & Filter

Applications

Chemical & corrosive waste handling

Marine & coastal environments

Food processing & wash-down areas

Any corrosive or high-moisture industrial setting