

Tipping Skips - Standard Range



Tipping Skips - Standard Range

Suitable for use across a multitude of industries, our forklift tipping skips keep working areas clear and enable safe, efficient removal of scrap, rubbish, or waste to the appropriate collection point.

Manufactured from robust 3mm gauge steel for exceptional durability and long service life.

Model Ref	Volumetric Capacity (m ³)	Load Capacity (kg)	Weight (kg)
RFS 40L	0.4	1000	125
RFS 80L	0.8	1000	175
RFS 120L	1.2	1250	188
RFS 160L	1.6	1500	219
RFS 200L	2.0	1500	240



Options

Lids

Auto Release

Mesh Extensions

Castors

Lifting Lugs

Drain Tap & Filter

Dimensions	O/all Length (mm)	O/all Width (mm)	O/all Height (mm)	Bin Length (mm)	Bin Height (mm)	Fork Spread (mm)
* RFS 40L	1360	800	780	1195	550	890
RFS 80L	1720	960	985	1545	760	890
RFS 120L	1720	1200	985	1545	760	890
RFS 160L	1720	1720	985	1545	760	890
RFS 200L	1720	2130	980	1545	760	890

Fork Section

150mm x 60mm

* For RFS 40L model, please note the overall width is 925mm. For all other models, the bin width is the widest point

Features & Benefits

- Full-width release handle eliminates need to lean between skip & truck
- Heavy-duty underframes for long service life
- Twin locking mechanism ensures skip remains secure when loaded unevenly
- Pre-drilled castors plates for easy retro-fitment (no welding required)
- Safety security chain to ensure safe retention to lift truck

